

IMAGE PROCESSING SOFTWARE

María Alejandra Bosio

Observatorio Astronómico
Universidad Nacional de Córdoba

ABSTRACT: A brief description of astronomical image processing software is presented. This software was developed in a Digital Micro Vax II Computer System.

RESUMEN: Se presenta una somera descripción del software para procesamiento de imágenes. Este software fue desarrollado en un equipo Digital Micro Vax II.

Key words: DATA ANALYSIS — IMAGE PROCESSING

I- INTRODUCTION:

From the mathematical view point an image can be represented by a 2-dimensional function $I(x,y)$ defined in a certain domain: $0 \leq x \leq r$, $0 \leq y \leq s$. According to this model a digital image is given by an rxs -dimensional array where each value is the brightness of an image point. This array is obtained from a 2-dimensional scanning of a photographic plate. A 2D-microdensitometer is needed for this purpose. As a result a sequential file containing the information is obtained.

II- SOFTWARE DESCRIPTION:

The system is structured in blocks as follows:

II.I Data base:

the microdensitometer output files (sequential format) must be packed before being used by the system. The packing operation causes the output files to be smaller than the original by 50%. The packed file has $N1$ records each of them containing $N2$ fields. $N1$ and $N2$ are respectively the row and column numbers selected during the scanning procedure. Each numerical value in the original file is converted to its ASCII value in the output one.

II.II- Processing system:

This is the execution block of the system in which the image processing is done. The user interacts with the system through the following commands:

- NEWIMAG:

Loads an image to memory and sets it as active or program image: first the system asks for file name; then the reading operation is executed.

- SENS:

Calculates the intensity array from the density array using the sensitometry file. The computation includes the average determination in each step, the approximation of the resulting point by a least-squares procedures and the density array conversion.

- HISTOGRAMA:

The image histogram is a powerful tool in image processing because it provides statistics information about the object in image. This command gives the possibility of calculating and drawing the image histogram.

- CONTRASTE:

This command is used to produce an image enhancement with a grey-level transformation. This operation is performed by a direct mapping of the original levels in others: this new levels are selected by determining the transference function.

- ECUAL:

This command is used to perform the active image histogram equalization. This procedure can be done by two ways:

UNIFORM: the output histogram is equivalent to one characterized by a gaussian distribution.

NON-UNIFORM: The output histogram shape is defined by the user.

In the first way the output levels W_k are given by:

$$W_k = \sum_{j=0}^k P_z(z_j) \quad \text{or} \quad W_k = \sum_{j=0}^k n_j/n$$

In second one a double transformation is needed: first a uniform equalization on input histogram, then a uniform equalization on output histogram and at last a composed mapping to have the output levels.

- SUAVIM:

This command makes image smoothing on the active image. It can be done by two ways:

- MEAN-VALUE FILTER : is the convolution operation between the active image and the pattern:

$$\begin{array}{ccc} 1/9 & 1/9 & 1/9 \\ 1/9 & 1/9 & 1/9 \\ 1/9 & 1/9 & 1/9 \end{array}$$

The central pixel is replaced by the average of itself and its eight neighbors if the difference between the new value and the original is smaller than a user specified threshold and not changed otherwise.

- MEDIAN-FILTER : each pixel is replaced by the median of itself and its eight nearest neighbors.

- ZOOM:

This command gives the active image ampliation and it can be done by two ways:

-WITHOUT INTERPOLATION : each original pixel is replaced by four identical pixels in the resultant image.

WITH INTERPOLATION : everyone of the tree new pixeles is obtained by a 2-dimentional interpolation of the original ones.

- PERFIL:

This command computes and draws the intensity profile in both directions : horizontal and vertical.

- REALCE:

This command gives the active image objects boundaries enhancement. This operation computes the convolution between the active image and a pattern that varies with the selected filter type. The possibilities are:

DIRECTIONAL FILTERS	[NORTH	NON-DIRECTIONAL FILTERS	[FOUR NEIGHBORS
	[SOUTH		[EIGHT NEIGHBORS
	[EAST		[LAPLACIAN
	[WEST		[HORIZONTAL
			[VERTICAL

- STORE:

Stores the active image or a pattern in one of the three memory pages.

- OPERAR:

Performes arithmetical (addition, subtraction) or logical (and, or) operations between active image and a memory page.

II.III Output:

This block transfers the processed information to output devices. Output devices are 4107 Tektronix Graphic Terminal, LN03 printer and Houston Plotter.

María Alejandra Bosio: Observatorio Astronómico de la Universidad Nacional de Córdoba, Laprida 854, (5000) Córdoba, Argentina.